

SOLTON

INTERNATIONAL Series

Neodym
Speakers
Bi-Amping

Light-Weight

*Powerful 2-way fullrange-cabinets
with amazing sound.*



For bands, disco, bars,
installation in- and outdoor use.
Schools, stadiums
60° x 40° horn radiation
Flying pionts



SOLTON INTERNATIONAL



Type

	Passive	Active	Passive	Active	Passive	Active
Configuration	2-way cabinet	2-way cabinet	2-way cabinet	2-way cabinet	2-way cabinet	2-way cabinet
Amping		Mono		Bi-amp		Bi-amp
Nom. impedance	8 Ohm	4 Ohm	8 Ohm	4 Ohm	8 Ohm	4 Ohm
Rated power RMS	160 Watt	160 Watt	250 Watt	250 Watt	300 Watt	300 Watt
Program power	320 Wattt	320 Watt	500 Watt	500 Watt	600 Watt	600 Watt
SPL 1W/1m	97 dB	97 dB	99 dB	99 dB	100 dB	100 dB
Frequency Range	50 Hz - 18 kHz	50 Hz - 18 kHz	50 Hz - 18 kHz	50 Hz - 18 kHz	45 Hz - 18 kHz	45 Hz- 18 kHz
Crossover frequ.	2,7 kHz	2,7 kHz	2,7 kHz	2,7 kHz	2,7 kHz	2,7 kHz
Comp. HIGH	1" driver	1" driver	1" driver	1" driver	1" driver	1" driver
Comp. LOW (MID)	10" Speaker	10" Speaker	12" Neodym	12" Neodym	15" Neodym	15" Neodym
Material	ABS	ABS	ABS	ABS	ABS	ABS
Handles	1	1	1	1	1	1
(W x H x D)	35 x 48 x 27	35 x 48 x 27	43 x 58 x 31,5	43 x 58 x 31,5	45 x 68,5 x 38	45 x 68,5 x 38
Weight (kg)	11 kg	13 kg	13 kg	17 kg	19 kg	22 kg



E-10 M



DJ's favourite
active monitor!

Features: EN-12 B/15 B

Integrated Bi-Amp amplifier,
Jack and XLR mic input (12" 1x mic / 15" 2x mic)
with gaincontrol, line input (XLR/chinch with levelcontrol),
bass-treble, mastergain, line out (XLR/Jack),
clip led, ground lift

Features: E-10 M

Integrated Mono-Amp amplifier,
1x Jack and XLR mic input
with gaincontrol, line input
(XLR/chinch with levelcontrol),
bass-treble, mastergain,
line out (XLR/Jack).



subject to change without prior notice - designed by SOLTON acoustic