

LUNARIS ACTIVE SERIES						
		LUN 12MA	LUN 15MA	LUN 12SA	LUN 15SA	LUN 18SA
LOUDSPEAKERS SPECIFICATIONS						
Components	High Low	12” Coaxial Woofer	15” Coaxial Woofer	12” Woofer	15” Woofer	18” Woofer
Construction	High-density MDF with high strenght water paint - Metal grill - 2 x handles for carrying comfort - Stand adaptor					
Dimensions	mm (WxHxD) in (WxHxD)	430x502x332 16,9x19,7x13	486x607x377 19,1x23,9x14,8	410x400x460 16,1x15,7x18,11	478x436x560 18,8x17,1x22	580x480x660 22,8x18,9x25,9
Weight	Kg - lb	20 - 44	29 - 63,9	23 - 50,7	32 - 70,5	40 - 88,1
AMPLIFIER SPECIFICATIONS						
Input	Sensitivity Impedance	+ 4dB 30KΩ (balanced) -15KΩ (Unbalanced)				
Crossover frequency	Hz 12dB/ott	2,8KHz	2,1KHz	150 Hz	150 Hz	150 Hz
Output power W Rms (1kHz,THD1%)	W High W Low	50 250	50 300	350	400	500
Distorsion	(THD + N)	<0.1%				
Controls	Volume control - Shield 4 PRESETS Selector (STAGE1-STAGE2-STAGE3-VOICE)			Volume control - Shield		
Connections	IN OUT	1 XLR-F + 1 JACK (Combo INPUT) XLR- M Link OUT See the label on the unit				
Power supply						
SYSTEM SPECIFICATIONS						
Frequency response	Hz (-10dB)	60-20KHz	50-20KHz			
Sensitivity	SPL (1W-1m) Max SPL	97dB 122dB	98dB 123dB	92dB 116dB	95dB 118dB	95dB 120dB
Dispersion	°	80x80	90x90			